

EGG INJECTION APPARATUS AND METHOD

by

Edward G. Bounds, Jr.

Cross References

1.P. This application claims the benefit of U.S. Provisional Application No. 60/036,042, filed January 21, 1997 and U.S. Patent Application No. 09/009,234, filed January 20, 1998, the contents of which are hereby incorporated by reference. This Application is a divisional application of U.S. Patent Application No. 09/009,234 filed January 20, 1998, ^{Now PAT. NO. 6,240,877.}

Background

This invention relates generally to the injection of eggs, referred to as "*in ovo*" injection, and more particularly concerns an apparatus and method for the automated injection of various substances into eggs, especially for the control of disease in avian flocks.

There are a number of reasons in the fields of both medicine and poultry husbandry, among others, for the injection of a range of substances into various types of eggs. For example, in the field of medicine, fertile, or embryonated, eggs are used to incubate and harvest biologicals which have medical applications, such as certain vaccines. Eggs provide an appropriate environment for the growth of the vaccines.

Another reason for the injection of eggs is to add substances to the embryo or to the environment around the embryo. The purpose is to induce beneficial effects in the subsequently hatched chicks. The substances which may be added include antimicrobials such as antibiotics, bactericides and sulfonamides; vitamins; enzymes; nutrients; organic salts; hormones; adjuvants; immune stimulators and vaccines. This technique can, for example, lead to an increased percentage of hatch. The chicks from eggs that are injected prior to hatch may retain a sufficient amount of the injected substance so there is no need to inject the hatched bird. The chicks may grow faster and larger and experience improvement in other physical characteristics.

In ovo injection has also proven effective as a means for disease prevention. A significant problem in the poultry industry is a high incidence of infectious diseases which increases the cull rate and causes a high rate of mortality during the growing stage of young birds. An example is Marek's disease, which is a widespread herpes virus-induced lymphoproliferative disease of chickens. It is standard practice in commercial hatchery operations to immunize birds post-hatch against diseases like Marek's prior to placing them in brooder houses. This is a very labor-intensive process. With the advent of *in ovo* injection, certain types of vaccination, such as Marek's, which in the past had been carried out on hatched poultry are now successfully performed on embryonated eggs.

In general, the *in ovo* injection technique involves delivering a substance in fluid form to the interior of an egg using a needle. Occasionally, the needle is used to both penetrate the egg shell and deliver the fluid substances. However, fine needles, which are preferred when precise

fluid delivery is required, may not be rigid enough to penetrate an egg shell. On the other hand, needles large enough and rigid enough to penetrate the egg shell may not provide suitable fluid delivery, both in terms of location and amount, which more delicate needles can provide. Furthermore, the penetrating process quickly dulls or plugs the needle. Therefore, a drill or punch is typically used to make a hole in the egg. Once the drill or punch has penetrated the egg shell, the needle is inserted into the interior of the egg for delivering the fluid substance.

An important parameter in *in ovo* injection is the location of the needle injection port within the egg at the time of fluid injection. Eggs are comprised of a brittle exterior shell and two flexible interior membranes. An outer membrane adheres to the interior of the shell and an inner membrane encases the fluid contents of the egg, including the allantois, amnion and yolk sac. At the time the egg is first laid, the two membranes are substantially coextensive. However, as the fertile egg is incubated, the inner membrane separates from the outer membrane, thereby forming an air cell between the two membranes, usually at the large end of the egg.

The egg can be injected at any location, and even into the embryo itself. The suitability of a particular location depends on the purpose for which the egg is being injected and the fluid substance delivered; since some substances must be delivered to a particular location within the egg in order to be effective. The problem with locating the needle at the appropriate injection point is that eggs vary in size. The resulting differences in distance between the shell and the location at which delivery of the fluid substance is desired complicates the task of consistently locating the injection point.

The amount of fluid delivered is also an important parameter. Typically, it is necessary that a sufficient amount of fluid be introduced into the egg to produce the desired effect. For example, in the case of bactericides, the amount of material introduced into the eggs must be sufficiently great to cause an appreciable increase in the percentage of hatch, but must not be so great that it kills or injures the embryos.

Automated apparatus and methods for injecting eggs are available. Generally, in such devices the eggs are brought under a bank of injectors housing needles and punches. First, the punches open a hole in the shell. Then the needle is inserted into the egg, followed by injection of fluid. A primary goal of automated *in ovo* injection is to be able to handle a high egg volume in a short period of time while consistently maintaining the amount and location of the fluid substance delivered within each of the eggs.

An automated device for injecting eggs must address the fact that eggs are not identical in size. Some devices include means for permitting vertical travel of the injectors relative to the apparatus to accommodate eggs of different sizes. However, another problem related to "*in ovo*" injection in commercial hatcheries is that the eggs are typically carried in setting trays, or "egg flats." Conventional egg flats comprise anywhere from 36 to 168 depressions for receiving the smaller end of the egg. Because the depressions are designed to accommodate the varying sizes of eggs, the eggs are free to wobble in the depression. As a result, the eggs may be slightly tilted with respect to the injectors. The capacity to accurately and precisely control the travel of a needle within the egg is diminished when the egg is tilted, even where the relative vertical travel

between the egg and the needle is carefully controlled to account for differences in egg height.

Methods for dealing with the tilted eggs include lifting the eggs free of the flat in a suction cup integral with the injector to properly orient the eggs with respect to the needles or allowing the injectors to translate through an arc to properly orient the injectors to the tilted eggs. The former is impractical and has never seen commercial application. The latter method is somewhat effective, but can fail in practice when an injector translates improperly, becoming so angled with respect to an egg that the needle will glance off the egg shell, completely missing the egg. Therefore, fluid delivery location still remains a problem for automated *in ovo* injection devices.

Another problem with existing *in ovo* injection machines is that the pump mechanisms for delivering the substances may produce excessive sheer and compressive forces on the substance. In the case of Marek's disease vaccine, which is commonly presented as a whole-cell suspension, these forces can rupture the cells and thereby render the vaccine virus inside the cells much less effective.

Another consideration in egg injection is that it must be done in as clean an environment as is possible so that there is reduced probability of bacteria or mold entering the egg during or after puncture. Since the same needle is used repetitively, there exists the possibility of cross-contamination. Accordingly, the needle must be sanitized periodically. The magnitude of this problem is exacerbated in the automated apparatus where the same needle is used to inject hundreds of eggs.

For the foregoing reasons there is a need for an automated egg injection apparatus and method which is less labor-intensive than known systems. The apparatus should handle a high volume of eggs with a high level of precision with respect to both the location and quantity delivered. Ideally, the injection needle should be capable of functioning as both the penetrating and fluid delivery means. Fluid delivery should be gentle and precise so as not to damage live vaccine cells. The overall operation should be sanitary so as to minimize, if not eliminate, cross-contamination. The machine design should facilitate both manufacture and operation, thus reducing manufacturing and operating costs as compared to known devices and methods.

Summary

The present invention comprises an apparatus and method for *in ovo* injection that satisfies these needs.

An apparatus for injecting fluid substances into eggs, having features of the present invention, comprises a plurality of injectors, disposed within each of the injectors are needles moveable between a retracted position and an extended injecting position with respect to the injectors; means for positioning the plurality of injectors in alignment with a corresponding plurality of eggs; means for advancing the injectors into engagement with the eggs; means for advancing the needles from the retracted position to the extended position into the eggs; means

for producing pulses of fluid substance through the needles; and means for retracting the needles from the eggs.

A feature of the egg injection apparatus is an injection assembly comprising one or more substantially horizontally-oriented plates with openings therethrough for holding the injectors substantially vertically in the openings in the plates, a lower portion of the injector depending downwardly below the plates and an upper portion of the injector resting at or above the plates. The openings in the plates are slightly larger than the cross-section of the injectors for permitting the injectors to move vertically within the openings in the plates with respect to the plates. An egg nesting cup is pivotally secured to the lower end of each injector. Means for raising and lowering the plates and the injectors are provided so that when the plates are lowered and the lower portion of the injector contacts an egg to be injected, the nesting cup seats against the egg and, while the plates proceed downwardly, the injector moves vertically upward with respect to the plate and the nesting cup is free to move independently of the injector body to seat around the egg. One of the plates may be horizontally moveable relative to the other plates after the plates have reached the limit of their downward movement for securing the injectors against movement.

An injector for use with an egg injecting apparatus is also provided, comprising an injector body, a needle disposed within the injector body, the needle moveable between a retracted position and an extended injecting position with respect to the injector body, an articulating cup pivotally secured to the end of the injector body, the articulating cup adapted for receiving the upper portions of the eggs, means for driving needle into the egg with sufficient force to pierce the egg shell, means for supplying fluid to the needle for delivery into the eggs after penetration to a predetermined distance, and means for retracting the needle from the egg. The relationship defined by the seated position of the articulating cup against the shell of an egg and the injecting position of the needle is consistently reproducible so that the penetration and injection location of the needle within an egg is consistent regardless of the size and orientation of the egg. A fastener pivotally secures the cup to the injector, the fastener having a sanitizing fluid reservoir defined by an annular recess at the upper end of the fastener.

A needle for use in the injector comprises a beveled, solid tip for penetration of the egg shell, and a radial opening adjacent the tip for delivery of fluid. The needle tip may be coated with titanium and beveled at an angle of from about 20 degrees to about 45 degrees.

Fluid delivery is accomplished via a pressurized fluid source, tubing carrying fluid from the pressurized fluid source to the needle, a first contacting member adapted to be rigidly connected to the egg injection apparatus and a second contacting member reciprocally connected to the first contacting member, wherein the tubing passes between the members for pinching the tubing closed when the contacting members are together and allowing fluid to flow through the tubing when the contacting members are apart. The volume of fluid delivered is controlled by the fluid pressure and the amount of time the contacting members are apart.

A spray assembly for applying sanitizing solution to the injectors and needles is provided, comprising a pan, a spray shield extending upwardly from the sides of the pan, the spray shield adapted to receive the injector assembly of the egg injection device, a plurality of

spray nozzles in the pan, means for supplying sanitizing fluid to the spray nozzles, and means for moving the spray nozzles back and forth across the pan during spraying for uniform coverage of the injector assembly.

A method for injecting fluid substances into eggs having features of the present invention comprises providing an injectable fluid substance, arranging a plurality of eggs in an egg flat, placing the egg flat containing eggs into an egg-receiving assembly in alignment with a plurality of injectors, each of the injectors housing a fluid delivery needle, vertically aligning the beveled delivery tip of each needle with an egg, positioning a plurality of injectors, including an articulating cup, in seating relation against portions of the shell of each egg, initiating vertical needle movement, moving the needle between a retracted position and an extended position with respect to the cup, the extended position piercing the egg through the shell and defining an injecting position within the egg, delivering a predetermined amount of fluid at the end of the needle stroke through the needle into the egg in measured amounts; and withdrawing the needles from the eggs.

The method may further comprise the step of positioning the injectors in a sanitizing shower following the step of injection and extending and retracting the delivery tips of the needles at least once during the sterilizing shower, and then repeating steps above.

Accordingly, it is an object of the present invention to provide a new apparatus and method for *in ovo* injection having one or more of the novel features of this invention as set forth above or hereinafter shown or described.

Similarly an object of this invention is to provide an automated apparatus and method for *in ovo* injection which is capable of injecting a high volume of eggs in a short time period.

It is an object of this invention to provide for the control of disease in avian flocks. Therefore, in one of its aspects, it is an object of this invention to inject beneficial substances into the embryo or to the environment around the embryo to improve the hatch rate and to induce beneficial effects in the subsequently-hatched chicks.

Another object of this invention is to provide a needle for use in *in ovo* injection which is sufficiently rigid and durable to repeatedly penetrate an egg shell and which provides appropriate substance delivery location and amount.

Still another object of this invention is to provide an *in ovo* injection apparatus and method for consistently and accurately controlling the location of the substance delivery needle at a predetermined injection point in the egg, regardless of the size of the egg or the tilt of the egg when in a conventional egg flat.

Further, an object of this invention is to so control the amount of material injected so as to provide the maximum amount of beneficial substances without damage.

Yet another object of this invention is provide gentle delivery of fluid substances to

minimize damage to whole-cell suspensions, such as Marek's vaccine.

A still further object of this invention is to provide an *in ovo* injection apparatus and method which reduces labor and minimizes manufacturing and operation costs.

Finally, an object of this invention is to provide for a sterile environment for *in ovo* injection so as to minimize cross-contamination.

The apparatus of the present invention provides a method for automatically injecting eggs with a desired fluid at a predetermined location within the egg. The vertically-movable injector further including an egg nesting cup accommodates the varying sizes of eggs and the slight tilt encountered with respect to vertical due to the design of egg flats. The injector is positioned with respect to the egg so that the same injection location is achieved despite the size and orientation of the egg. The present invention is capable of accurately controlling the travel of the needle within the egg. A solid-tipped needle can be used for egg shell penetration and injection thereby eliminating the need for a separate punch. Radial outlet ports on the needle prevent direct fluid impingement on the embryo. The preferred fluid delivery method also eliminates the pumping of fluids through conventional fluid-handling systems and offers both precise and cell-safe fluid delivery. Few live cells are destroyed in the delivery, ensuring that an effective quantity of vaccine titer reaches the egg. A clean injection environment is maintained since all egg contacting surfaces are sanitized after each injection cycle. This minimizes the potential for cross-contamination of the eggs. The egg injection apparatus of the present invention is simple to manufacture and operate. Labor is reduced from known methods and devices while at the same time improving output.

Brief Description of the Drawings

For a more complete understanding of this invention reference should now be had to the embodiments illustrated in greater detail in the accompanying drawings and described below.

In the drawings:

FIG. 1 is a perspective view of an embodiment of the egg injection apparatus of the present invention;

FIG. 2 is a perspective view of an egg flat;

FIG. 3 is a front elevation view of the egg injection apparatus shown in FIG. 1;

FIG. 3A is a front elevation cross-section view of the left side portion of FIG. 3 showing a sanitization assembly for use in the present invention;

FIG. 4 is a rear elevation view of the left rear portion of the egg injection apparatus shown in FIG. 1 with an egg pallet and egg flat in place wherein background items are removed for clarity;

FIG. 4A is an elevation view showing an automatic start mechanism partially in cross-section;

FIG. 5 is an elevation view in cross-section of the right portion of the bridge assembly and right linear shaft mount;

FIG. 5A is a top plan view of the bridge transition plate of FIG. 5;

FIG. 6 is an elevation view in cross-section of the a second embodiment of the right portion of the bridge assembly and right linear shaft mount;

FIG. 6A is a top plan view of a bridge transition plate of FIG. 6;

FIG. 7 is a rear elevation view of an injection assembly for use in the present invention;

FIG. 8 is a left side elevation view of the injection assembly shown in FIG. 7;

FIGS. 9A, 9B and 9C are partial side elevation, rear and top views, respectively, of tooling plates, a gripper plate and air cylinder for use in the present invention;

FIG. 10 is a top end view of an injector body and egg nesting cup for use in the present invention;

FIG. 10A is an elevation view of the injector body shown in FIG. 10 taken along line 10A-10A;

FIG. 11 is an elevation view of a needle guide sleeve for use in the present invention;

FIG. 12 is a side elevation view of a needle for use in the present invention;

FIG. 13 is a cross-sectional view of an injector for use in the present invention resting in the tooling and gripper plates and in position on an egg;

FIG. 13A shows the same view as FIG. 13 with the tooling and gripper plates lowered and the needle extended into the egg;

FIG. 14 is similar to FIG. 13 including a light spring around the lower portion of the injector;

FIG. 14A shows the same view as FIG. 14 with the tooling and gripper plates lowered and the needle extended into the egg;

FIG. 15 is a top plan view of a pressurized chamber base plate for use in the present invention;

FIG. 16 is a partial elevation view of a fluid manifold and pincher assembly for use in the present invention;

FIG. 16A is a partial cross-section view taken along line 16A- I 6A of FIG. 16; and

FIG. 17 is a partial rear view of an embodiment of the egg injection apparatus of the present invention with the rotator assemblies thereof pivoted into upright positions.

Description

The term "birds," as used herein, is intended to include males or females of avian species, but is primarily intended to encompass poultry which are commercially raised for eggs or meat, or to breed to produce stock for eggs or meat. Accordingly, the term "bird" is particularly intended to encompass either gender of any bird, including without limitation, chickens, ducks, turkeys, geese, quail, ostriches, pheasants, and the like. The present invention may be practiced with any type of bird egg.

The term "fluid," as used herein, is intended to include any material which will flow and is not limited to pure liquids. Thus, "fluid" refers to solutions, liquid-liquid suspensions, liquid-solid suspensions, gases, gaseous suspensions, emulsions, and any other material or mixture of materials which exhibits fluid properties. Certain solid materials also fall under this term, such as biodegradable polymers (e.g., in the form of syringeable beads) which release active agents upon biodegradation.

An egg injection apparatus embodying features of the present invention is shown in FIG. 1, and denoted generally by the numeral 20. A structural base unit 22, having a front end 34 and a rear end 42, provides support and strength to the apparatus 20. The base unit 22 includes a plurality of upright leg members 24. The upright leg members 24 support a rectangular horizontal bracket assembly 26 comprised of strut members 28. Extending upwardly from the corners of the horizontal bracket assembly 26 are upright support members 30. The upright support members 30 support U-shaped linear shaft mounts 32 on each side of the base unit 22. Horizontally mounted on the inboard side of each of the linear shaft mounts 32 is a lower cylindrical linear shaft 40 which extends the length of the linear shaft mounts 32. As seen in FIG. 1, a second upper, linear shaft 38, which is above and parallel to the cylindrical linear shaft 40, is carried by the far linear shaft mount 32. The second linear shaft 38 comprises a double-acting rodless servopneumatic cylinder. A rubber bumper 33 is mounted on the outside of the linear shaft mounts 32 and wraps around the ends of the apparatus 20.

The upright support members 30 at the rear 42 of the base unit 22 extend upwardly and are joined at the top by an upper frame member 44 forming a rear control area. An operator works from the rear 42 of the apparatus 20. A control panel 46, including buttons, switches, visual liquid crystal display (LCD) and indicator lights, is provided on the rear upright support members 30 and upper frame member 44, as shown. Brackets 47 for additional control panels are available. The entire apparatus 20 is mounted on casters or wheels 48 so that it can be

moved from place to place, as desired. A brake or floor lock 50 is provided to hold the apparatus 20 in place during operation.

A framework 70 (see also FIG. 4) for receiving eggs to be injected is mounted on the top portion of the horizontal bracket assembly 26. Preferably,, the framework 70 is designed to receive one or more conventional incubation egg flats used in commercial hatcheries. For example, FIG. 2 shows a "ChickMaster®54" egg flat 90 capable of holding fifty-four eggs in nine offset rows of six depressions 91 each. The flat 90 also includes several projections or spacers 92.

Returning to FIG. 1, the framework 70 is designed to receive a large egg pallet 54 that is capable of supporting three of the egg flats 90 shown in FIG. 2. Therefore, the egg pallet 54 shown in FIG. 1 accommodates three "ChickMaster® 54" egg flats 90. The egg pallet 54 is sized to slide between longitudinal clamps on the framework 70 for securing the egg flats 90 in a predetermined position, as will be described further below.

A bridge assembly 100 is slidably mounted on the linear shafts 38, 40 above the egg receiving framework 70. In operation, a pressurized gas is supplied to the rodless servopneumatic air cylinder 38 for propelling the bridge assembly 100 back and forth along the air cylinder 38 and linear shafts 40 above the eggs.

An injection assembly 120 is carried on the bridge assembly 100. The injection assembly 120 comprises a vertically reciprocating bank of injectors 300. Each of the injectors 300 houses a reciprocating needle for supplying a fluid substance to the interior of the eggs. The number and location of the injectors 300 preferably correspond in number and location to the egg-holding depressions in each egg flat 90. This configuration allows injection of all of the eggs in a flat at one time.

Since the design of egg flats may vary, it is understood that any number of injectors 300 may be provided in the injection assembly 120 as long as the injectors are arranged so as to correspond to the locations of the egg-holding depressions 91 in a particular egg flat 90. For example, some one-piece egg flats hold as many as one hundred sixty eight eggs. When injecting such a large number of eggs in this type of egg flat, the injection assembly 120 could conveniently hold fifty six injectors 300 thus requiring three injection sequences to complete the flat. This type of large egg flat would not require the underlying egg pallet 54.

When an injection cycle is initiated, the bridge assembly 100 moves from a "home" position at the front 34 of the base unit 22 and rapidly traverses along the linear shafts 38, 40 to the rear 42 of the base unit 22 to a position directly over the first egg flat 90. The bridge assembly 100 stops when it is so positioned that each injector 300 is directly above one of the eggs in the flat 90. The bank of injectors 300 is then lowered so that the injectors contact the eggs.

Once the injectors 300 are seated on the eggs, the needles are extended a predetermined distance with sufficient force to penetrate the egg shell. The needles continue

through the openings in the egg shells to an injecting position. Fluid is delivered to each egg via one or more radial outlet ports in each of the needles. Following fluid delivery, the needles retract and the injectors 300 are returned to their "up" position away from the eggs in the flat. The bridge assembly 100 moves to a position over the next egg flat for injection, and so on, until the eggs in the last egg flat have been injected. The bridge assembly 100 then returns to the "home" position adjacent the last egg flat.

Of course, the injection sequence can proceed in opposite fashion beginning with the eggs in the flat adjacent the "home" position of the bridge assembly 100, proceeding sequentially to the rear 42 of the base unit 22 and then returning to the "home" position. However, the former injection cycle with the injection sequence commencing at the rear 42 of the base unit 22 has been found to be faster.

Fluid substances to be injected, such as vaccines, are ordinarily provided in a closed, sterile plastic bag having ports (not shown), similar to an IV bag. The bag is suspended from a hanger 122 mounted on the injection assembly 120. The bag is housed in a pressurized chamber 200. Fluid delivery from the fluid bag to the needles is accomplished via flexible fluid delivery tubes. The fluid delivery tubes are not shown in the figures to avoid unnecessary complication. The routing and number of tubes is apparent from this description. All fluid delivery tubes between common points are substantially the same length so that there is no variation in internal fluid friction. Therefore, fluid is equally distributed to each individual injector 300 at substantially the same time. This allows for consistent delivery of the proper dosage of fluid to the eggs.

The front 34 of the base unit 22 is shown in FIG. 3. The linear shaft mounts 32 (FIG. 1) are separated by a frame spreader member 36. A sanitization assembly 240 is mounted to the base unit 22. When the bridge assembly 100 is in the "home" position at the front 34 of the base unit 22, the injection assembly 120, with the injectors 300, is directly over the sanitization assembly 240. The sanitization assembly 240 comprises a spent fluids sump pan 242 and a spray shield 244. The spray shield 244 is secured to and extends upwardly from all sides of the sump pan 242 for preventing spray from leaving the sanitization assembly 240 area. The sump pan 242 includes a narrow drain channel having a drain outlet 248 which drains spent sanitizing fluid from the pan 242 and to a spent fluids reservoir 250 on the lower front of the base unit 22.

A spray manifold 252 (FIG. 3A) extends the length of the sump pan 242. A plurality of spray nozzles 256 are aligned along the top of the manifold 252. A sanitizing fluid supply pipe 258 is threaded into the side of the manifold and slidably extends through a hole 260 in the side of the sump pan 242. The end of the pipe 258 connects to a sanitizing fluid supply tube leading from a pump 264 (FIG. 3) secured to the base unit 22. The pump 264 pumps sanitizing fluid from a sanitizing fluid reservoir 266 on the lower front of the base unit 22 to the spray nozzles 256.

Referring to FIG. 3A, the spray manifold 252 with spray nozzles 256 is shown, including caster wheels 254 on each end of the manifold 252. A sanitizing fluid supply pipe 258 is threaded into the side of the manifold and slidably extends through a hole 260 in the side of the

//

sump pan 242. Means are provided for moving the spray manifold 252 back-and-forth across the sump pan 242. Specifically, a double-acting rodless air cylinder 267, including a carriage 269 and a linear slide 271, is mounted to the base unit beneath the sump pan 242. An L-shaped bracket 268 is provided, having one end secured to the carriage 269 of the rodless air cylinder 267. The other end of the bracket 268 is attached to the sanitizing fluid supply pipe 258.

Sanitization is performed between each injection cycle to minimize cross-contamination of the eggs. Spray sanitization is initiated when the bridge assembly 100 reaches the "home" position. The bank of injectors 300 is lowered until the injectors 300 are surrounded by the spray shield 244. The needles extend and the sanitizing fluid pump 264 is activated generating a v-shaped spray of sanitizing fluid, from each of the nozzles 256, which overlap to provide complete coverage of the bank of injectors 300. As the spray continues, the rodless air cylinder 267 moves the manifold 252 from a position on the left side of the sump pan 242, as seen in FIG. 3A, to the right side of the sump pan 242, as shown in dotted lines. When the manifold 252 reaches the right side of the sump pan 242, the needles retract and then re-extend. The air cylinder 267 then returns the manifold 252 to the left side of the sump pan 242, the spraying stops and the needles retract. A dwell time of at least about 10 seconds follows the stoppage of spray before the injection assembly 90 is allowed to commence another injection cycle, in order to allow adequate time for the sanitizing fluid to kill bacteria.

Along with a uniform spray pattern, a spray with sufficient force is preferred for dislodging solid matter which may be picked up from, for example, an exploded or broken egg. Multiple spray nozzles mounted in the bottom of the sump pan underneath the injectors may also be used. However, the preferred means described above affects more thorough coverage, especially towards the perimeters of the injectors.

After the sanitization sequence has been completed, the apparatus 20 is ready for another injection cycle. A new set of egg flats has, by this time, been placed in the framework 70 by the user, preferably during the sanitization sequence, and the injection cycle is repeated.

Each of the sub-parts of the apparatus 20 of the present invention is described in more detail below. The scope of the invention is not intended to be limited by the materials listed here, but may be carried out using any material which allows the construction and operation of the apparatus described herein.

Preferably, a source of pressurized gas is used to drive the apparatus of the present invention. The pressurized gas is generally air or nitrogen, although for the purpose of this description it will be assumed that the pressurized gas is air. The bridge assembly 100, injector assembly 120, needles and sanitization assembly 240 movement are all carried out pneumatically. As seen in FIG. 1, electrical and pneumatic enclosures 60, 62 are mounted on the rear 42 lower portion of the base unit 22 for housing appropriate equipment. Air is supplied at an air supply inlet 64 mounted adjacent the exterior of the pneumatic enclosure 62. The air supply inlet 64 is connected to the source of pressurized air (not shown), such as instrument air, an air compressor or the like. From the air supply inlet 64, the pressurized inlet air initially passes through a series of air filters where the inlet air is filtered and most of the moisture and oil

content removed. The clean dry air then flows through an air pressure regulator for controlling the operating pressure of the apparatus. The inlet air supply pressure is preferably from about 100 psi to about 120 psi. The inlet air supply pressure may be monitored by an air pressure switch (not shown) and visually indicated on an air pressure gauge (not shown).

On the side of the bridge assembly 100 adjacent the injector assembly 120 is an electropneumatic enclosure 124 for housing the electrical and pneumatic components required for operation of the bridge assembly 100 and injection assembly 120. A robotic cable carrier, such as an e-chain (not shown), may be provided for uncomplicated transition of the pneumatic and electrical lines from the electrical and pneumatic enclosures 60, 62 to the bridge assembly 100 and electropneumatic enclosure 124.

Air cylinders referred to herein, and their connection to the parts they move, are generally conventional in nature and will not be described in further detail other than to point out that the appropriate arrangements can be made without undue experimentation in manufacturing or operating the device. It is understood that other devices, such as solenoids, could be used in the present invention, but single or double-acting fluid driven pneumatic cylinders are preferable since egg injection machines are typically washed down after each use.

The egg injection apparatus 20 is controlled by an onboard computer or central programmable logic controller (PLC). The programming of the operation of the egg injection apparatus 20 is easily accomplished from the logical operation of the apparatus as described herein. The PLC controls the normal operation of the unit. The operation of the pneumatic cylinders, pneumatic control valves, operator interface, LCD, indicator lights, buttons and switches are all controlled by the PLC. Sensors for air pressure and fluid levels may also be provided. Proximity sensors selectively mounted at various points on the apparatus signal the position of the moving parts of the apparatus to the PLC for various machine functions.

A suitable egg-receiving framework 70 for use in the present invention has been previously described by the applicant in his U.S. Patent Nos. 5,107,794 and 5,247,903, issuing April 29, 1992 and September 28, 1993, respectively, the contents of which are hereby incorporated by reference. As seen in FIG. 4, the apparatus for use in the present invention is nearly identical to that shown in the patents, with modifications for making an egg flat clamp moveable for holding the egg pallet 54 and egg flats securely in place and an automatic start mechanism. The egg flat clamps comprise an outer active clamp 72, an inner passive clamp 74 and flanking saddle members 84 which support the egg pallet 54 and egg flats 90. Air cylinders 78 are provided for reciprocating one or more push rods 80 secured to the active clamp 72 for moving the active clamp 72 inwardly against the egg pallet 54 and egg flats 90 to grip them. Fine adjustment for properly securing egg flats of different widths is provided for using screws 82 passing through the passive clamp 74 and the adjacent saddle member 84. This allows the distance between the passive clamp 74 and the saddle member 84 to be changed. A roller 86 may be provided on the screws 82, especially for ChickMaster® egg flats, to support the portion of the egg flats 90 and egg pallet 54 which overhang the saddle member 84. Thus, the preferred framework 70 is able to accommodate all conventional egg flats.

The automatic start mechanism 460 is visible between the saddle members 84. The automatic start mechanism (FIG. 4A) includes a contact plate 462 and a spring-loaded plunger 464. The contact plate 462 is pivotally-mounted to a bracket 466 fixed to the egg receiving framework 70 between the saddle members 84 and adjacent an end stop member 76. The plunger 464 fits vertically through a hole in the bracket 466. A nylon cap nut 468 is threaded onto the upper end of the plunger 464 and engages the underside of the contact plate 462. A spring 470 is positioned between the cap nut 468 and the bracket 466 for biasing the plunger 464 and the contact plate 462 upward. The lower end of the plunger 464 fits slidably through a guide sleeve 472 positioned against the lower surface of the egg receiving framework 70. A radial pin 474, extending through the plunger 464, defines the maximum upward extension of the plunger 464. A proximity sensor 476 is mounted to a strut member 28 adjacent the lower end of the plunger 464 for sensing the plunger end when the plunger 464 is depressed.

Initially, the active clamp 72 (FIG. 4) is in an outermost position to accept the egg pallet 54 bearing the flats 90. The egg pallet 54 is pushed forward supporting the egg flats 90 until the forward-most egg flat contacts the end stop member 76 and all of the egg flats are tightly aligned end-to-end. Sliding the pallet 54 in place also pivots the contact plate 462 in a clockwise direction, as seen in FIG. 4A, driving the plunger 464 downward against the force of the spring 470. When the lower end of the plunger 464 is adjacent the proximity sensor 476, the proximity sensor signals the PLC to initiate the injection cycle. Upon initiation of the injection cycle, the active clamp 72 (FIG. 4) is drawn inwardly against the egg flats 90, securing the egg flats in a predetermined position with respect to the injection assembly 120. As an alternative to the automatic start mechanism, a manual start button may be provided on the rear control panel 46 for actuation when the egg pallet 54 is in place against the end stop member 76.

Turning now to FIGS. 5 and 5A, there is shown an elevation view in cross-section and a top plan view, respectively, of the right portion of the bridge assembly 100. The bridge assembly 100 comprises two spaced, parallel horizontal cross members 102 which are secured to one another at their bottom ends by bridge stabilizer plates 104. Spanning the top ends of the horizontal cross members 102 are bridge transition plates 106 which extend beyond the ends of the horizontal cross members 102. A bridge stiffener 108 is secured between the stabilizer plates 104 and the transition plates 106. The bridge assembly 100 is positioned between the linear shaft mounts 32 so that the bridge transition plates 106 are above and parallel to the lower linear shafts 40. Mounted on the front and rear bottom of the bridge transition plates 106 are linear bearing pillow blocks 116 which ride on the lower linear shafts 40. The bridge transition plate 106 carries a floating riser 111 in a retaining yoke 109 for attaching to the servopneumatic air cylinder 38 carriage 113 (FIG. 5A).

A servopneumatic linear drive serves as a positioning means for the bridge assembly 100. The servopneumatic drive conventionally includes a linear encoder embedded in the rodless air cylinder barrel 38. As the piston (not shown) moves in either direction, the linear encoder signals the position of the bridge assembly 100 to an electronic controller. The controller compares the actual cylinder position with setpoint values and sends an electronic signal to a servopneumatic valve. The servopneumatic valve regulates the flow of air to the cylinder 38 in direct proportion to the electronic signal received from the controller. The controller is

programmed to stop the bridge assembly at predetermined points along the linear shaft mounts 32 positioning the injection assembly 120 so that each injector 300 is directly over an egg. When the eggs in the last egg flat are injected, the linear encoder signals the controller to return the bridge assembly 100 to the "home" position. A suitable servopneumatic rodless air cylinder and drive for use with the present invention are available from Festo Corporation of Hauppauge, New York, U.S.A. A proximity sensor 119 is mounted in a bracket 118 on the bridge transition plate 106 and serves as a back-up for the linear drive.

An elevation view in cross-section and a top plan view of the right portion of the bridge assembly of another embodiment of the bridge drive mechanism is shown in FIGS. 6 and 6A, respectively. In this embodiment, upper linear shafts 38, comprising rodless air cylinders, are mounted parallel to the lower linear shafts 40 on both linear shaft mounts 32. The bridge transition plates 106 carry a floating mount 110 and riser 112 for attaching to the rodless air cylinder carriages 114.

Means are also provided in this embodiment for stopping the bridge assembly 100 at any point along the linear shafts 38, 40 directly over an egg flat 90. The locating means is shown in FIG. 6A and includes an index mechanism 270 secured to the top of each of the bridge transition plates 106. The index mechanism 270 comprises a saddle mount 272, an index carriage 274 and a strike bar 276. The saddle mount 272 is a U-shaped bracket secured to the bridge transition plate 106. The carriage 274 is a block which slides on two bearing shafts 278 mounted in parallel spaced relation across the upstanding legs of the saddle mount 272. An air cylinder 280 is fastened to the inner leg of the saddle mount 272, and the cylinder rod is connected to the carriage 274 to provide reciprocating movement to the carriage 274. The strike bar 276 is connected to the side of the carriage 274 and extends beyond the carriage 274. When the index carriage 274 is in an outermost position, the end of the strike bar 276 extends beyond the edge of the bridge transition plate 106.

The bridge transition plates 106 also carry two proximity sensors 284, 286. One of the proximity sensors 286 is positioned in a hole in the upstanding leg of the saddle mount 272. Metal plates, or "index flags," 290 are mounted on the inner surface of the linear shaft mounts 32 at each selected intermediate stop of the bridge assembly 100. Adjacent each index flag 290 is a stationary cam roller 292 secured with a carriage bolt (not shown) in a T-slot which extends the length of each linear shaft mount 32 (FIG. 6A). The index flags 290 and cam rollers 292 can be positioned at any point along the linear shaft mounts 32 for exact positioning of the bridge assembly 100 at selected intermediate points along the linear shafts 32.

As the bridge assembly 100 approaches a pair of index flags 290, the first proximity sensors 284 sense the index flags 290 and send a signal to the PLC. The PLC reverses the air flow to the rodless air cylinders 38. As a result, the bridge assembly 100 is rapidly decelerated in the next few inches of travel. When the second proximity sensors 286 come upon the index flags 290, the PLC is again signaled to reverse the air flow to the rodless air cylinders 38. Immediately thereafter, the strike bars 276 contact the stationary rollers 292 and the bridge assembly 100 is held solidly in position over an egg flat 90, with each injector 300 directly over an egg. By momentarily reversing the air flow, the bridge assembly 100 comes to a gentle stop

against the cam rollers 292, allowing high transition speeds between stopping points. After the eggs in an egg flat are injected and the bank of injectors 300 ascends to the "up" position, the strike bar 276 is momentarily retracted allowing the bridge assembly 100 to move to the next stopping point. When all of the eggs in the last egg flat at the front 34 of the base unit 22 have been injected, the bridge assembly 100 returns to the "home" position.

The injection assembly is shown in FIGS. 7 and 8. The injection assembly 120 comprises a stationary vertical thruster assembly 140 and a vertically reciprocating injector thruster assembly 170. The vertical thruster assembly 140 includes two lower horizontal members 142 spanning the horizontal cross members 102 of the bridge assembly 100. Vertical members 144 extend upwardly from each end of the lower horizontal members 142 and support front and rear upper horizontal members 146. A large U-shaped bracket 148 is secured across the upper horizontal members 146. A vertically thrusting air cylinder 150 is centrally disposed in the bracket 148 with the cylinder rod 152 extending through the bracket 148. A stroke length adjuster 154 is threaded to the upper end of the cylinder rod 152. A lock nut 156 is provided for fixing the location of the stroke length adjuster 154. Bumpers 158 are placed on the cylinder rod 152 on either side of the bracket 148.

The lower end of the cylinder rod 152 is secured to a central horizontal member 172 of the injector thruster assembly 170. The central horizontal member 172 serves as an air manifold with each end having an air inlet 174 and nine air outlets 176 on each side for distributing air to injector air cylinders, as will be described below. Horizontal end members 178 are secured to the ends of the central horizontal member 172. Cylindrical slide bars 180 depend downwardly from each end of the horizontal end members 178. Spaced parallel upper and lower tooling plates 182 are secured to the bottom of the slide bars 180. A gripper plate 350 is mounted adjacent the upper tooling plate 182. The tooling plates 182 and gripper plate 350 include a plurality of openings 183 corresponding in position to egg holding depressions in the egg flat 90. A proximity sensor 184 is mounted in the bottom of the U-shaped bracket 148 for sensing when the central horizontal member 172 is adjacent the bracket 148 indicating that the injector thruster assembly 170 is in the "up" position. The proximity sensor 184 signals the PLC to permit movement of the bridge assembly 100 to the next injection position, or to return to the "home" position.

Referring now to FIGS. 9A, 9B and 9C, the gripper plate 350 is slidably mounted adjacent the upper tooling plate 182 on flange bearings 352 fastened to the upper tooling plate 182. Plastic slip bearings 354 are provided between the upper tooling plate 182 and the gripper plate 350 for smooth relative movement. The gripper plate 350 holes 183 are slightly larger than the tooling plates' holes 183. An o-ring 358 is disposed in an annular groove in each gripper plate hole 183. An elongated yoke 360 is secured across one end of the gripper plate 350. Opposed air cylinders 362 are mounted between the tooling plates 182. The air cylinder rods 364 are fastened to the ends of the yoke 360 by a pin 366.

The injector 300 comprises a high density polyethylene injector body 302 (FIGS. 10 and 10A), an air cylinder 304 (FIG. 13), an egg nesting cup 306 (FIG. 10A), a needle guide sleeve 326 (FIG. 11) and needle 308 (FIG. 12). The injector body 302 and egg nesting cup 306

are shown in FIGS. 10 and 10A. A coaxial bore 310 of varying diameter extends the length of the injector body 302, including first and second reduced diameter bore portions 312, 313. Three vent holes 320, 322, 324 are provided in the injector body 302. The upper vent hole 320 and lower vent hole 324 allow sanitizing fluid to drain. The middle vent hole 322 functions as an air vent for the lower vent hole 324.

The egg nesting cup 306 is frustoconical in shape. The egg nesting cup 306 is secured to the injector body 302 by a swivel bolt, or needle guide sleeve 326 (FIG. 11). For this purpose, the second, lower reduced diameter portion 313 of the injector body bore 312 is tapped and a heli-coil inserted for receiving the needle guide sleeve 326 and securing the egg nesting cup 306 to the bottom end of the injector body 302. When in place, there is a slight gap between the injector body 302 and nesting cup 306, as seen in FIG. 10A. The inner portion of the egg nesting cup 306 is also frustoconical in shape and is sized so that the eggs do not make contact with the needle guide sleeve 326. Generally, this can be accomplished in most cases using a preferred angle of the inner cone between about 80 degrees and about 100 degrees.

The lower end 303 of the injector body 302 and the upper surface 307 of the nesting cup 306 are angled away from their respective axial centers. The needle guide sleeve 326 allows the egg nesting cup to swivel freely with respect to its vertical axis and the injector body 302. Preferably, the lower 303 and upper 307 surfaces of the injector body 302 and the nesting cup 306, respectively, are cut away at an angle of at least seven degrees which permits the nesting cup 306 to swivel sufficiently to seat around an egg regardless of its orientation in the egg flat 90, even at the worst possible tilt. Less swiveling action than this could result in the top surface 307 of the nesting cup 306 contacting the bottom surface 303 of the injector body 302 and less than full circular contact of the nesting cup 306 around the top of the egg.

The inner end 327 of the needle guide sleeve is chamfered. The chamfered end 327 of the needle guide sleeve 326 acts as a reservoir for holding sanitizing fluid. An important feature of the present invention is that each time the needle 308 retracts during the sanitization sequence, fresh sanitizing fluid is drawn up into the reservoir 327 in the needle guide sleeve 326 by capillary action or surface tension on the needle cannula. The lowermost vent hole 324 allows old sanitizing fluid to escape as new fluid is drawn into the reservoir 327. Therefore, each time the needle retracts after injecting an egg, the end of the needle 308 is bathed in residual sanitizing fluid which helps to minimize cross-contamination of the eggs.

The needle 308 for use in the present invention is shown in FIG. 12. The upper end of the needle 308 is bonded through the center of a plastic Luer male hub fitting 334. The upper end of the fitting 334 includes a barbed flange 336 for connection to an appropriate fluid delivery tube so that fluid can be delivered to the needle 308 and to the egg. The needle tip 338 is beveled and plugged as high as the bottom of one or more radial outlet ports 340, preferably with a vinylester epoxy for strength. The beveled tip 338 is desirable since this type of needle 308 will tend to shear a hole in the egg starting at the very point of the tip. After the initial break-through, the needle tip 338 shears the remainder of a round hole, often creating a flap of shell at the hole.

The needle 308 is sufficiently large that the needle 308 can penetrate thousands of

egg shells without bending, yet is thin enough to meter very small amounts of fluid in a precise manner. Preferably, the needle 308 used in the present invention is from about 12 gauge to about 20 gauge. A needle thicker than about 12 gauge could create cracks in the egg shell while a needle thinner than about 20 gauge is ordinarily too thin to repetitively penetrate an egg shell without bending. For example, a needle which is about 18 gauge (0.050 inches) is suitable, since this size fulfills all requirements. At the preferred needle thickness, the preferred bevel angle is from about 20 degrees to about 45 degrees. At angles less than about 20 degrees, the contact area between the needle tip 338 and the surface of the egg shell becomes large, thus requiring more force to break through the shell and possible cracking of the shells. Bevel angles greater than about 45 degrees necessitate positioning the radial outlet ports 340 farther from the tip 338. When the ports 340 are closer to the tip 338, the depth of penetration into the egg and the possibility of injection into the air cell, which reduces the benefit of the injected substance, are minimized. A suitable bevel angle is about 30 degrees which allows location of the radial outlet ports 340 about 0.1 inches from the needle tip 338 and leaves room at the heel of the tip 338 for filler. The needle is preferably stainless steel and the outside of the tip of the needle may be titanium-plated partially along its length. This allows the same needle to be used for a large number of injections without loss of sharpness or damage, usually evidenced by burrs on the leading edge of the needle tip 338. Alternatively, a pencil-point needle may be used.

As shown in FIGS. 13 and 13A, an injector 300 fits substantially vertically in each opening 183 in the tooling plates 182 and gripper plate 350. As seen in FIG. 13, the openings 183 in the tooling plates 182 and gripper plate 350 are slightly larger in diameter than the diameter of the injector body 302 to allow vertical movement of the injector 300 relative to the plates 182, 350.

The upper, larger diameter portion of the bore 310 (FIG. 10A) loosely receives a singleacting spring return air cylinder 304. The lower end of the air cylinder 304 is threadably received in the first reduced diameter inner bore portion 312 (FIG. 10A). The upper vent hole 320 serves as an air outlet for the cylinder 304. A plastic ring 314 surrounds the upper end of the air cylinder 304 above the upper tooling plate 182 and is sandwiched by o-rings 316. The top of the injector body has an annular groove 318 (FIGS. 10 and 10A) for receiving a third o-ring 316. The o-rings 316 seal the plastic ring 314 against the upper end of the injector body 302 when the air cylinder 304 is threaded into place in the injector body 302.

The air cylinder rod 305 and needle guide sleeve 326 have an axial hole 332 (see FIG. 11 for sleeve 326) for receiving the needle 308. The male Luer fitting 334 at the top of the needle 308 is received in a complementary metal female Luer fitting 335 at the upper end of the cylinder rod 305 so that the needle 308 and air cylinder rod 305 move together. It is understood that a threaded fitting would also accomplish this result. The hole in the air cylinder rod 305 and the hole 332 in the needle guide sleeve 326 are only slightly larger than the outside diameter of the needle 308, thereby providing lateral support to the needle 308 for penetrating an egg shell. This diameter differential also allows easy removal and replacement of the needle 308 from a position on top of the injector thruster assembly 170. A suitable air cylinder having an axial hole is available from Bimba Manufacturing Company, of Monee, Illinois, U.S.A., as part number D57441-A.

When the bridge assembly 100 is in position over an egg flat 90, the air cylinder 150 on the vertical thruster assembly 140 lowers the injector thruster assembly 170 and thus the injectors 300 toward the eggs. As the injector thruster assembly 170 descends two things happen. First, the swiveling egg nesting cups 306 receive and seat around the upper, large ends of the eggs. Because the egg nesting cups 306 swivel, the nesting cups 306 adjust to the position of the eggs as the injector assembly 170 descends, regardless of the orientation of the eggs in the egg flat 90. This allows the nesting cups 306 to make complete contact around the perimeter of the ends of the eggs.

Secondly, each injector 300 adjusts vertically to the height of the egg by virtue of the vertical movement of the injector 300 in the plates 118, 350. The stroke length adjuster 154 (FIG. 8) preferably limits the vertical stroke of the injector thruster assembly 170 so that the injectors 300 rise with respect to the plates 182, 350 about one inch, after making contact with the eggs. However, since the injectors 300 can move independently of one another, the injectors 300 rise to different heights so that different sizes of eggs can be accommodated even within the same egg flat. Further, because the design of the conventional egg flat dictates the center of rotation for each egg within the egg flat depression, the egg nesting cup 306 functions to align the center of rotation of the egg with respect to the needle 308 regardless of the orientation of the egg. Because of this alignment and along with the simultaneous vertical adjustment of the injector 300, the needle 308 will always extend to substantially the same point within the egg relative to the egg's center of rotation. The injection assembly 120 thus provides means for aligning the egg beneath the injector in a predetermined position with respect to the needle. Further, the depth and location to which the needle 308 penetrates is similarly predetermined by the distance of the center of rotation of the egg from the end of the injector 300. This ensures consistent penetration and injection location of the needle 308 within the egg regardless of variations in egg size and orientation.

When the injector thruster assembly 170 completes its downward travel the gripper plate air cylinder 362 (FIG. 9A) is activated moving the yoke 360 and gripper plate 350 outward. This movement forces the gripper plate o-rings 358 against the injector bodies 302 thereby holding the injectors 300 securely in position against the tooling plate holes 182 (FIG. 13A). Narrow horizontal grooves (not shown) machined in both the injector body 302 and the upper tooling plate holes 183 intermesh to help prevent vertical movement of the injectors 300. Thus, once the injectors 300 rise with respect to the descended plates 182, 350 to accommodate egg height, the gripper plate 350 clamps the injectors 300 in place, preventing the injector 300 from lifting off of the eggs. Otherwise, the injectors 300 could lift off of the eggs when the needles 308 make initial contact with the shell and then fall back down on the eggs as the needles 308 penetrate the egg shells, possibly cracking the egg shell.

Next, the needle air cylinder 304 is activated by pressurized air carried to the injectors 300 from the air outlets 176 (FIG. 8) in the central horizontal member of the injector thruster assembly 170. The air delivery tubes from opposed outlets deliver air to the injectors at opposite ends of a row of injectors 300. All of the injectors in the row are connected in series. This configuration evenly distributes line pressure and enables all the needles to extend and retract substantially at the same time. When the air cylinder 304 is activated, the needles 308

extend out of the injector body 302 a predetermined distance and with sufficient force to cause the beveled tip 338 of the needle 308 to shear through the egg shell. The needle 308 continues through the opening in the egg shell to an injecting position (FIG. 13A). The distance the needle 308 moves is determined by the stroke length of the air cylinder rod 305. The distance the needle tip 338 extends beyond the end of the injector body 302 may be adjusted by varying the thickness of the plastic ring 314. Alternatively, or additionally, washers of varying thickness' may be fitted between the plastic ring 314 and the air cylinder 304.

Once the air cylinder rod 305 and needle 308 reach maximum extension, fluid is injected into the egg through the radial outlet ports 340 (FIG. 12). The needle 308 retracts from the egg when air pressure is released from the needle air cylinder 304. At the same time as the needle 308 retracts, the gripper plate 350 is released and the plates 182, 350 and injector thruster assembly 140 (FIG. 8) move to the "up" position. The proximity sensor 184 senses the injector thruster assembly 140 is in the "up" position and signals the PLC to move the bridge assembly 100 over the next egg flat or return to the "home" position.

As shown in FIGS. 14 and 14A, a coil spring 328 may be provided surrounding the lower end of the injector body 302 and seated against a flange 330 on the nesting cup 306 and the lower tooling plate 182. The spring 328 provides mild resistance to the swiveling action of the egg nesting cup 306 and vertical movement of the injector body 302. The positive mechanical locking feature of the gripper plate 350 allows the use of a very light spring 328 which reduces the possibility of cracking or crushing fragile egg shells. Preferably, the spring is no more than about 1.5 lbs of force at full compression.

When ChickMaster[®] egg flats 90 are used, a vertically sliding egg flat detector bar, not shown, is provided through the tooling plates 182. Most conventional egg flats interlock end-to-end, with the exception of some ChickMaster[®] egg flats. Therefore, a ChickMaster[®] flat can be put in backwards and the injectors 300 will not align with the eggs. Attempting to inject the eggs under these circumstances will bend the needles. If the ChickMaster[®] flat is in the proper position, the egg flat detector bar will engage one of the egg flat spacers 92 (FIG. 2) as the injector thruster assembly 170 descends driving the detector bar upwardly. A proximity sensor, not shown, is mounted in the injector thruster assembly 170 and senses the detector bar when it is in the "up" position. The proximity sensor signals the PLC that injection of the eggs may proceed. If the ChickMaster[®] egg flat is in backwards, the detector bar will not engage the egg flat spacer 92 and will remain in the "down" position. Operation is stopped, the active clamp 72 opens and, if desired, an alarm or display is generated signaling the operator to pull the egg flats out and reverse the offending flat.

The above description is the preferred means for moving and locating the bridge assembly 100 and injection assembly 120. However, there may be applications in which the eggs are moved towards a stationary bank of needles. Also, the relative movement of the eggs and bridge assembly 100 and injection assembly 120 need not be carried out by the particular apparatus illustrated and described herein as any assembly which provides appropriate relative movement between the eggs and the needles is possible including, for example, a chain and sprocket mechanism or a servomotor or stepper motor drive with a timing belt or ball screw

linear actuator. However, since the machine is preferably washable, pneumatic drive is preferred over electrical drive motors. An important feature of any suitable system is the proper, highly accurate positioning of the injection assembly and the eggs prior to injection so that each injector is aligned with an egg.

Referring back to FIGS. 7 and 8, the pressurized chamber 200 is shown and comprises an acrylic body 202, cap plate 204 and base plate 206. The cap plate 204 fits against a shoulder 208 in the top of the body 202 and has a chamfered bottom edge for seating against an o-ring 212 disposed in a groove in the top of the body 202.

As seen in FIG. 15, the base plate 206 includes a large base portion 216 and an integral circular upper plate 218. The base plate 206 is fastened to a base mount 222 which extends across the U-shaped bracket 148 of the vertical thruster assembly 140. Holes 230 are provided in the base plate 206. One of the holes 230 has dual o-ring grooves for accepting a fluid delivery tube for a fluid outlet and to ensure that the pressurized chamber 200 is air-tight. Two other holes are threaded for a pressurized air inlet and a pressure relief safety valve, respectively.

The chamber body 202 fits down over the circular upper plate 218 until a shoulder 224 (FIG. 7) in the bottom of the body 202 engages the circular base plate 218. The seal between the chamber and base consists of a large o-ring 223 mounted on the periphery of the upper plate 218. The body 202 is held in place by rotating the body so that ears on the base of the body 202 fit into locking dogs 228 on the base plate 206 (FIG. 15). More than one fluid delivery tube hole or pressurized chamber may be provided in the event that one or more fluids are to be injected into the eggs.

The fluid delivery tube projects downward through the base plate 206 carrying fluid under pressure from the bag and chamber. The fluid delivery tube splits and carries fluid to dual high density polyethylene manifolds 380 (FIGS. 16 and 16A) secured across the top of the horizontal end members 178 of the injector thruster assembly 170 (FIG. 8). Each manifold 380 has a fluid inlet 382 for each fluid to be injected, and enough fluid outlets 384 to supply fluid for half of the injectors 300. The ends of the manifold include a plug 388 to the first fluid outlet 384 to eliminate dead space.

A fluid delivery tube for each injector 300 extends from a barbed fitting 386 in each outlet 384 and passes between cooperating stationary 390 and dynamic 392 pincher plates. The stationary pincher plate 390 is secured beneath the manifolds 380 to the underside of the horizontal end members 178 of the injector thruster assembly 170. The dynamic pincher plate 392 is slidably mounted on spaced, parallel linear guide shafts 394 extending from the ends and middle of the stationary pincher plate 390. The middle shaft 394 passes slidably through the stationary pincher plate 390 and is connected to an air cylinder rod 396 to draw the pincher plates 390, 392 together to pinch off the fluid delivery tubes. Vaccine tube guide plates 398 having a hole for each tube are positioned on the top and bottom of each stationary pincher plate 390 to maintain the alignment of the delivery tubes and smooth movement of the pincher plates 390, 392.

Normally the pincher plates 390, 392 are closed, pinching off the fluid delivery tubes. The only time the pincher plates 390, 392 open is immediately after the needle 308 reaches the injection location in the egg. At this point, the air cylinder 400 connected to the middle bearing shaft 394 is activated; and the pinchers 390, 392 open, allowing fluid from the pressurized fluid bag to flow through the hoses and needles into the egg. The pinchers remain open for a specific time, allowing a predetermined amount of fluid to be delivered into the egg, and then the pinchers 390, 392 close. The fluid quantity delivered may be precisely controlled by the amount of pressure on the fluid bag within the pressurized chamber 200 and the length of time the pinchers 390, 392 remain open.

Of course, other means for delivery of predetermined amounts of fluid can be used including, for example, infuser cuffs wrapped around the fluid bag or metered injection pumps. Infuser cuffs function much like the pressure chamber described above, squeezing the bags to drive the fluid. However, infuser cuffs sometimes suffer from non-uniform fluid flow as the fluid bag empties since fluid flow slows considerably when the bag is less than about half-full. Therefore, uniform flow throughout all dosages as the bag empties is not possible. The preferred method empties the fluid bag while providing the same precise delivery amount until the bag is empty. Metered injection pumps, such as peristaltic pumps, are very precise in the amount of fluid delivered. However, such pumps suffer from a tendency to destroy live vaccine cells which can be crushed by the action of the pumps. For example, peristaltic pumps compress the fluid lines, increasing the probability of crushing live vaccine cells and diminishing the effectiveness of the fluid delivered. The preferred pincher plates, described above, have only a single tangent compression point and will disrupt very few cells. Therefore, the preferred fluid delivery method eliminates the pumping of fluids through conventional fluid handling systems and offers both precise and cell-safe fluid delivery.

The apparatus of the present invention described herein provides a method for automatically injecting eggs with a desired fluid at a predetermined location within the egg. The method of the present invention is applicable to any bird egg, and particularly those which are commercially reared for meat or egg production. Any substance may be efficiently and precisely injected into the egg, including without limitation antimicrobials such as antibiotics, bactericides, sulfonamides; vitamins; enzymes; nutrients; organic salts; hormones; adjuvants; immune stimulators; vaccines and the like.

The scope of the method of the present invention extends to immunization against all immunizable avian diseases, whether of viral, bacterial or other microbial origin. Birds which are reared in high density brooder houses, such as broiler and layer chickens, are especially vulnerable to infectious agents and would largely benefit from pre-hatch vaccination. Examples of such, without limitation, are Marek's disease, infectious bronchitis, infectious bursal, Newcastle disease, adenovirus diseases, reovirus, pox, laryngotracheitis, influenza, infectious coryza, fowl typhoid and fowl cholera. Vaccinating avian embryos potentially increases hatchability and livability during grow-out.

The apparatus and method of the present invention further contemplate means for transferring the eggs following injection from the egg flats into a hatching tray. The preferred

means for transferring the eggs is disclosed in U.S. Patent Nos. 5,107,794 and 5,247,903, referred to above, the egg-receiving framework 70 forming a part thereof. As described therein, and in connection with FIG. 17, active and passive rotator assemblies transfer eggs from the egg flats to a hatching tray. Handles are provided on each of the rotator assemblies for rotating the assemblies from their rest to their transfer positions. However, automated transfer is preferred for use in the present invention. Accordingly, pneumatic active and passive rotary actuators 414, comprising pneumatic double rack-and-pinion 180-degree rotation rotary actuators, are secured to the strut members 28 of the horizontal bracket assembly 26. Pivoted transfer arms 416 connect the rotary actuators 414 to linkage brackets 418 on the u-shaped support members 420 of the rotator assemblies 410, 412.

The transfer step can occur simultaneously with the spray sanitization cycle. The operator initiates transfer by placing a hatcher tray 94 over the eggs in an upside-down position. A frame member 422 positioned about midway along the horizontal bracket assembly 26 supports a photovoltaic cell and sensor. The sensor is tripped when the hatcher tray 94 is placed over the eggs signaling the PLC to start the transfer operation. First, the passive rotary actuator 414 rotates the passive rotator assembly 412 clockwise until it is in place over the eggs. The rotator assemblies 410, 412 are automatically latched together. The passive rotary actuator 414 reverses and the active rotary actuator 414 is activated swinging both rotator assemblies 410, 412 counterclockwise -180 degrees and depositing all of the eggs in the hatcher tray 94. The rotator assemblies 410, 412 are automatically disengaged and the active rotary actuator 414 brings the active rotator assembly 410 and empty egg flats back to the rest position. A proximity sensor 424 signals the PLC that the active rotator assembly 410 is in the rest position. The active clamp 72 opens allowing the operator to remove the egg pallet 54 and empty egg flats.

The total time required for the injection cycle, from securing the egg flats in place to removing the empty flats, is about 16 seconds. It is estimated that with the apparatus and method of the present invention one trained operator can inject over 20,000 eggs per hour.

The present invention has many advantages, including providing an egg injection apparatus comprising an injector designed to position itself in relation to an egg so that the injection location within the egg is precise and consistent. The articulating egg nesting cup ensures that the needle extends to the same region within the egg despite the orientation of the egg in the egg flat. Because the design of the conventional egg flat dictates the axis of rotation for each egg within its depression in the egg flat, the relationship defined by the seated position of the cup against the egg can position the extended needle at a predetermined location within the egg with respect to the center of rotation of the egg. Because the center of rotation remains relatively fixed with respect to the needle and the vertical adjustment of the injector ensures that the needles always extend to a predetermined depth inside the egg regardless of egg size, the tip of the needle will always extend to what is substantially the same point with respect to the center of rotation of the egg. Thus, a plurality of eggs can be consistently injected at a desired location, both horizontally and vertically, regardless of individual differences in egg size and orientation.

The precision with which the apparatus of the present invention can position the injection site allows for vaccination into areas previously too small for reliable, consistent

injection location, such as the allantois. Injection into the allantois offers advantages. For example, injection into the allantois in the fourth quarter of incubation allows for biologically effective injections without damage to the embryo which can be caused by impact of the needle if the injection is made into the larger, amniotic area which immediately surrounds the embryo itself.

The needle design of the present invention allows for egg shell penetration without a punch or drill. The solid needle tip allows the tip to be less sharp and still penetrate thousands of egg shells. Moreover, the larger bore possible with the large gauge needle allows fluid to be delivered with less shear forces.

The fluid delivery system of the present invention moves fluids through the system under low internal line pressure without pumping. Fluid is injected rapidly. The radial outlet holes can prevent direct fluid impingement on the yolk and embryo. Moreover, due to the low internal line pressure, hydraulic shear is minimized and cell integrity maximized. This is important since vaccine efficacy is dose-related and depends on cell integrity in vaccines such as for Marek's disease. Thus, the apparatus of the present invention is particularly useful in vaccine delivery since the apparatus will destroy fewer cells in the delivery process and therefore a higher actual vaccine titer will be delivered.

The apparatus and method of the present invention also offer a very sanitary injection environment. All egg contact surfaces are sanitized frequently. The sanitary environment minimizes the potential for cross-contamination of eggs. Moreover, the sanitization system is designed to be independent of the injection system thereby eliminating congested tubing. The positioning of the spray nozzles along the manifold and the traversing of the manifold across the sump pan insures complete, uniform coverage of the sanitization fluid on all portions of the injector which touch the eggs during the injection process. The sanitization spray directly impinges both sides of the needles and the outside edges of the egg nesting cups. The radial outlet holes of the needle prevent spray from entering the needle and potentially killing live cells or vaccine virus.

Further, radial egg transfer of the injected eggs from the egg flats to the hatcher is a vast improvement over the known egg transfer method using vacuum cups. The vacuum cups potentially provide an easy path for cross-contamination of the eggs. In the present invention, after the egg is injected, the only other object to touch the eggs is the sanitary hatcher tray. Thus, a possible path for cross contamination is eliminated. Moreover, the apparatus of the present invention is easily cleaned in a few minutes, as opposed to the vacuum cups and manifold which must be disassembled and placed in an aerated chemical bath for more than 30 minutes. The apparatus of the present invention effects a marked increase in productivity. The simplicity of the egg handling path reduces labor. One operator can perform all necessary operations, whereas the known technology requires two operators who have to continuously coordinate their tasks carefully for smooth and efficient operation. The present invention also allows feeding several egg flats at one time instead of the known technology of feeding one egg flat at a time on a moving conveyor. The present method frees the operator to perform other tasks after he has loaded the eggs into the apparatus. Outputs are greater than with double the labor on the current

machine. The apparatus of the present invention is simply built resulting in a decrease in manufacturing and operating cost over known devices and methods. Although the apparatus and method of the present invention have been described in considerable detail in connection with preferred embodiments thereof, it will be understood, of course, that I do not intend to limit the invention thereto since modifications may be made by those skilled in the art, particularly in light of the foregoing teachings. On the contrary, I intend to cover all alternatives, modifications and equivalents as incorporate those features which constitute the essential features of these improvements as may be included within the spirit and scope of my invention.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
222